

MADE IN TAIWAN

SERIES 32 PENUMATIC THREE WAY DIVERTER VALVE

ANSI 150#, DIN PN 10/16, JIS 5K/10K

- Ball and Cock Type
 - Stainless steel body construction
 - Size range
- 2" to 10" Ball Type
2" to 14" Cock Type



FIG. 32B BALL TYPE



FIG. 32C COCK TYPE

STAINLESS STEEL GATE VALVE Outside screw & Yoke bolted bonnet flanged ends

ANSI 150#, ANSI 300#, DIN PN 10/16, JIS 10K, JIS 20K

Size range

ANSI 150# / JIS 10K 1/2" to 24"

ANSI 300# / JIS 20K 1/2" to 16"

PN 10/16 1/2" to 12"

Design Standard

API 603

Shell wall thickness ANSI B16.34

Face to face ANSI B16.10, DIN 3202, JIS B2002

Flanges to ANSI B16.5, DIN 2501 JIS B2210



ANSI 150# / JIS 10K



ANSI 300# / JIS 20K



DIN PN 10/16

STAINLESS STEEL GLOBE VALVE Outside screw & Yoke bolted bonnet flanged ends

ANSI 150#, ANSI 300#, DIN PN 10/16, JIS 10K, JIS 20K

Size range

ANSI 150# / JIS 10K 1/2" to 16"

ANSI 300# / JIS 20K 1/2" to 10"

PN 10/16 1/2" to 12"

Design Standard

Shell wall thickness ANSI B16.34

Face to face ANSI B16.10, DIN 3202, JIS B2002

Flanges to ANSI B16.5, DIN 2501, JIS B2210



ANSI 150# / JIS 10K



ANSI 300# / JIS 20K



DIN PN 10/16